## FC05

## RILEVATORE PRESENZE - RFID - PIN

## The robust time & attendance control access JOB COSTING

The FC05 thanks to a wide range of communication modes meet all needs. Terminal interface is based on exchange of files and commands. Easy GUI interface is similar to tablet and smartphone experience. The operating system provides great performance. It has weather resistant case, reliability and low cost.



- HTTP/HTTPS and web services client. Easy way to control terminal using on-line mode with HTTP server.
- HTTP server terminal configuration using standard browser.
- Client Web browser take and display on-line information from HTTP/HTTPS server.
- Client SQL and MySQL send transit logs directaly to network DB.
- Client SMTP able to send mails.
- FTP client upload file to a FTP server according build-in scheduler.
- FTP Server terminal control by a FTP client.
- USB 2.0, Ethernet 10-100 Mbps, WiFi, UMTS modem and RS232, RS485.
- Badge supported: magnetic ISO 1-2-3, RFID 125 Khz and Mifare 14443-A, 14443-B, biometric technology.
- Full VGA TFT display.

BCST is a leading Italian company of manufacturing time attendance and control access terminals. BCST provides great flexibility on the customization of their products according to customer's requirement.

## CARATTERISTICHE TECNICHE PRINCIPALI:

- LCD VGA 8" 800 x 600 TFT 65536 colors Display with white led back-light
- Capacitive Touch-screen with 3.5 mm glass protection resistant to vandalism
- Keyboard with 18 keys
- Two RGB multi-color semaphore
- Polyphonic stereo audio
- Build-in 2 x RFID 125 Khz and 2 x 13.56 Mhz reader Mifare/NFC
- Build-in biometric optical reader
- DDR3 512 Mbyte memory
- 1 Ghz Cortex A8 CPU
- High precision temperature-compensated real time clock
- · Linux operating system
- 10-100 Auto-MDIX Ethernet
- 2 x USB 2.0 port
- Three serial communication ports RS232/485
- Two internal relays
- · 2 digital inputs
- Internal UMTS dongle
- Internal WiFi dongle
- · External USB plug for pen-drive
- PoE and direct 240 Vac
- Size W H D 210 x 230 x 80

